



## PM-5133

### 3.5" Touchscreen 3-phase Smart Power Meter

## Introduction

The PM-5133 series is a touch-screen 3-phase smart power meter specifically designed for industrial automation and energy management applications. Featuring a 3.5-inch high-resolution color TFT touch screen, it enables users to intuitively monitor power data and control demand to comply with contracted capacity requirements, fulfilling the needs of carbon inventory reporting and ISO-50001 energy management. This product offers comprehensive power measurement capabilities, including a voltage range of up to 500VAC, support for open-type current transformers (CT) with input currents up to 400A, bi-directional kWh measurement, true RMS measurement, multi-wiring energy consumption analysis, and power measurement accuracy better than 0.5% (PF = 1). It also supports Total Harmonic Distortion (THD) measurement, ensuring high-precision and visualized energy management. Additionally, the PM-5133 series provides advanced power information logging with timestamps, 1-hour demand trend visualization, and contracted capacity pre-warning with relay alarm linkage. With support for 32 sets of event and alarm notifications, it enables flexible system integration and remote monitoring for optimized power management.

## Specifications

System	
Real Time Clock(RTC)	Yes
Data Logger	
Time Stamp	Yes
Time Interval	1 second to 24 hours
Max. Records	638,586 records 7.39 days @ 1 second, 443 days @ 1 minute 24 power parameters per record (selectable)
AC Power Measurement	
Wiring	3P4W-3CT, 3P3W-2CT, 3P3W-3CT, 1P2W-1CT, 1P3W-2CT
Loops	3-phase: 1; 1-phase: 3 @ 1P2W-1CT, 1 @ 1P3W-2CT
Measurement Voltage	10 to 500 V
Measurement Current	-005 (0.05 A ~ 5 A); -100 (0.05 A ~ 60 A); -160 (0.1 A ~ 100 A); -240 (0.15 A ~ 200 A); -360 (0.3 A ~ 300 A); -400 (0.3 A ~ 400 A)
Measurement Frequency	50 Hz (Range 45 to 55 Hz)/ 60 Hz (Range 55 to 65 Hz)
W Accuracy	Better than 0.5% (PF=1)
Power Parameter Measurement	True RMS voltage (Vrms), True RMS current (Irms), Active Power (kW), Active Energy (kWh), Apparent Power (kVA), Apparent Energy (kVAh), Reactive Power (kVAr), Reactive Energy (kVArh), Power Factor (PF), Frequency (45 to 65 Hz)
Data Update Rate	1 Second
Communication	
RS-485	Protocol: Modbus RTU Baud Rate: 9600, 19200 (default), 38400, 115200; DIP Switch Selectable Data Format: N,8,1 (default); N,8,2; E,8,1; E,8,2; O,8,1; O,8,2 Isolation: 3000 VDC
USB	Type C Connector; USB 1.1 Client (Firmware updates only)


## Features

- Bi-directional Energy
- True RMS Power Measurements
- Energy Analysis for 3P4W, 3P3W, 1P3W, 1P2W
- W Accuracy Better than 0.5% (PF=1)
- Total Harmonic Distortion (THD)
- 3.5" High-resolution color touch screen
- Provides time-stamped power information logging function
- 1-hour demand trend display and contract capacity warning
- 2 Power Relay outputs triggered by defined alarm
- Offers 32 alarms or events information display




Alarm Output	
Power Relay	Form A (Normal Open) x 2; Relay Contact Voltage Range: 5 A @ 250 VAC (47 to 63Hz), 5 A @ 30 VDC
HMI	
LCD Display	3.5 TFT (Resolution 240 x 320, 65535 colors)
Backlight Life	20,000 hours
Brightness	270 cd/m2
LED Indicators	Yes, 1 Alarm LED
Touch Screen	Yes
Reset Button	Yes
Rotary Switch	Yes(Firmware updates only)
Rubber Keypad	5 keys(Programmable)
Buzzer	Yes
Power	
Power Input	+12 to 48 VDC
Power Consumption	3 W
Mechanical	
Casing	Plastic
Dimensions (mm)	119 x 115 x 54 (W x L x H)
Ingress Protection Rating	Front Panel: IP65
Installation	DIN-Rail Mounting and Panel Mounting
Panel Cut-out (mm)	90 x 90, +1/-0
Environment	
Temperature	Operating Temperature: -20 to +50 °C Storage Temperature: -25 to +80 °C
Humidity	10% to 90% RH, Non-condensing

## Appearance



## Dimensions (Units: mm)



## Ordering Information

RS-485 Interface	
PM-5133-005P CR	3.5" Touch LCD screen, Modbus RTU, 3-phase power meter; includes 5A CT (Inside diameter 10 mm; wire lead 4 m) x 3 (RoHS)
PM-5133-100P CR	3.5" Touch LCD screen, Modbus RTU, 3-phase power meter; includes 60A CT (Inside diameter 10 mm; wire lead 4 m) x 3 (RoHS)
PM-5133-160P CR	3.5" Touch LCD screen, Modbus RTU, 3-phase power meter; includes 100A CT (Inside diameter 16 mm; wire lead 4 m) x 3 (RoHS)
PM-5133-240P CR	3.5" Touch LCD screen, Modbus RTU, 3-phase power meter; includes 200A CT (Inside diameter 24 mm; wire lead 4 m) x 3 (RoHS)
PM-5133-360P CR	3.5" Touch LCD screen, Modbus RTU, 3-phase power meter; includes 300A CT (Inside diameter 36 mm; wire lead 4 m) x 3 (RoHS)
PM-5133-400P CR	3.5" Touch LCD screen, Modbus RTU, 3-phase power meter; includes 400A CT (Inside diameter 36 mm; wire lead 4 m) x 3 (RoHS)